




### Y-piece

Abzweige eingeschweißt  
ähnlich DIN EN 10253-3

short name: YP.\*




### technical product sheet

| D     | s   | l   | kg     | Art.-Nr.   |
|-------|-----|-----|--------|------------|
| 21,3  | 2,0 | 25  | 0,060  | YP-021-020 |
| 26,9  | 2,0 | 29  | 0,124  | YP-026-020 |
| 33,7  | 2,0 | 38  | 0,139  | YP-033-020 |
| 42,4  | 2,0 | 48  | 0,301  | YP-042-020 |
| 48,3  | 2,0 | 57  | 0,340  | YP-048-020 |
| 48,3  | 2,6 | 57  | 0,397  | YP-048-026 |
| 60,3  | 2,0 | 64  | 0,420  | YP-060-020 |
| 60,3  | 2,6 | 64  | 0,686  | YP-060-026 |
| 76,1  | 2,0 | 76  | 0,638  | YP-076-020 |
| 76,1  | 2,6 | 76  | 0,820  | YP-076-026 |
| 88,9  | 2,0 | 86  | 0,860  | YP-088-020 |
| 88,9  | 2,6 | 86  | 1,120  | YP-088-026 |
| 114,3 | 2,0 | 105 | 1,500  | YP-114-020 |
| 114,3 | 2,6 | 105 | 1,725  | YP-114-026 |
| 114,3 | 3,0 | 105 | 2,100  | YP-114-030 |
| 139,7 | 2,0 | 124 | 1,964  | YP-139-020 |
| 139,7 | 2,6 | 124 | 2,419  | YP-139-026 |
| 139,7 | 3,0 | 124 | 2,980  | YP-139-030 |
| 168,3 | 2,0 | 143 | 2,650  | YP-168-020 |
| 168,3 | 2,6 | 143 | 4,500  | YP-168-026 |
| 168,3 | 3,0 | 143 | 5,050  | YP-168-030 |
| 219,1 | 2,0 | 178 | 4,412  | YP-219-020 |
| 219,1 | 3,0 | 178 | 7,010  | YP-219-030 |
| 273,0 | 3,0 | 216 | 9,160  | YP-273-030 |
| 323,9 | 3,0 | 254 | 13,800 | YP-323-030 |
| 355,6 | 3,0 | 279 | 17,000 | YP-355-030 |
| 406,4 | 3,0 | 305 | 23,000 | YP-406-030 |

available material: 1.4571

Y-piece/ X-piece > Y-piece

**Y-bend**

with welding ends

**Feature**

manufactured from pipe EN 10217-7

laser cut

MIG welded

immersion pickled

dimensional range DN 10 bis DN 600

optional wall thickness up to 5,0 mm

material 1.4307/304L - 1.4571 - 1.4404/316L

base material certificate acc. EN 10204/3.1

Varinox GmbH | Revision date 08.10.2025 | Revision number 41 ([t 026])

