




Y-bend 45°, welded

from two bends 45° Type 5D

ähnlich DIN EN 10253-3

short name: YB45*



technical product sheet

D	s	r	kg	Art.-Nr.
33,7	2,0	73,0	0,165	YB45-033X20-4
42,4	2,0	93,0	0,189	YB45-042X20-4
48,3	2,0	108,0	0,195	YB45-048X20-4
60,3	2,0	135,0	0,414	YB45-060X20-4
76,1	2,0	175,0	0,760	YB45-076X20-4
88,9	2,0	205,0	1,157	YB45-088X20-4
114,3	2,0	270,0	1,882	YB45-114X20-4
114,3	2,6	270,0	2,000	YB45-114X26-4
139,7	2,6	330,0	3,250	YB45-139X26-4
139,7	3,0	330,0	3,700	YB45-139X30-4
168,3	2,6	390,0	4,100	YB45-168X26-4
168,3	3,0	390,0	5,200	YB45-168X30-4
219,1	3,0	510,0	8,540	YB45-219X30-4
273,0	3,0	625,0	13,486	YB45-273X30-4
323,9	3,0	775,0	19,290	YB45-323X30-4

available material: ask

Y-bend > 45° (Type 5D)



Y-bend

with welding ends

Feature

welded from two bends 45° Type 5D ($r=2,5xD$)

laser cut

MIG welded

immersion pickled

dimensional range DN 10 - DN 600

wall thickness 2,0 bis 5,0 mm

materials 1.4307/304L - 1.4571 - 1.4404/316L

inspection certificate basic material acc. EN 10204/3.1